

PF5750SR Specification Sheet



Accessories to consider...

Caution signs
(hgv height also available)



Sign Post
(call for info & pricing)



Specification:

- Traffic calming speed ramp

Product material:

- Recycled pvc

Weight:

- End cap 2.7kg mid section 8.6kg

Fixings:

- Universal fixings for tarmac or concrete (supplied)
- Central segments require 4no bolts
- End caps require 2no bolts

Key features:

- Package included end caps, mid sections and fixings
- Integral cable trunk
- Non-slip textured surface
- Embedded cats eyes as standard
- High visibility yellow sections contrasting with pure black sections

The PF5750 Speed Ramp 50mm or 75mm variants

The PF5750 speed ramp is manufactured from heavy duty recycled PVC segments.

The design offers early visual warning and provides a highly effective method of restricting speed.

The speed ramp is available in two alternate heights, consequently applying differing speed restrictions, with the 50mm version reducing vehicles to speeds of 15-20 mph and the 75mm version reducing vehicles to speeds of 5-10 mph.

The PF5750 can be laid in multiple lengths by simply interlocking each of the 500mm wide sections

securely with four fixing bolts for extra stability.

The 75mm option also includes a centre run cable tunnel for temporary traffic lights, fair grounds, water supplies etc.

It is recommended that signage is used in conjunction with speed ramps to warn on coming traffic.



EVERY EFFORT HAS BEEN MADE IN PREPARATION OF THIS SHEET HOWEVER WE HOLD NO RESPONSIBILITY FOR ERRORS OR OMISSIONS.